




Attributes

Highlights	Description
<ul style="list-style-type: none"> ▪ Fast delivery ▪ High repeatability ▪ Zero backlash with speed optimised transmission ratio ▪ Hollow shaft thru center of rotational axis ▪ Preloaded ball bearing 	<p>The MaalonDrive® Hollow 8mm - type 2 micro positioning gear is characterised, in particular, by its hollow shaft, yet with minimal outer dimensions. Optical or electrical signals can be guided through the hollow shaft on the central rotary axis of the gear, thereby allowing a simple and space-saving design to be realised. At the core of this micro gearbox is a zero-backlash MaalonDrive® gear with a reduction ratio of 120:1. The preloaded ball bearings on both the input shaft as well as the output shaft result in precise guiding and allow the application to be directly connected.</p>

Technical parameter

P-029



Technical Supply Specifications: MaalonDrive® Hollow 8mm - Type 2



Micromotion GmbH, Phone: +49 (0) 6431 – 569 18 – 25, E-mail: sales@micromotion.de

Nr.	Parameter	Symbol	Value	Hint
P-003	Ratio	i	120 : 1	
P-004	Self-locking		yes	
P-006	Hollow shaft		1	
P-008	Repeatability unidirectional		15 arcsec	
P-009	Repeatability bidirectional		20 arcmin	
P-010	Accuracy		20 arcmin	
P-011	Transmission accuracy		30 arcmin	
P-013	Torsional stiffness		2.67 $\frac{\text{Nm}}{\text{rad}}$	
P-014	Lost motion		20 arcmin	
P-015	Backlash		0 arcmin	
P-016	Rated torque	T	18 mNm	
P-017	Peak torque	T	37 mNm	
P-018	Momentary peak torque	T	92 mNm	
P-021	Rated input speed	n	15000 rpm	
P-022	Maximum input speed	n	50000 rpm	
P-023	Rated output speed	n	125 rpm	
P-024	Maximum output speed	n	416.667 rpm	
P-026	No-load starting torque	T	97.5 μNm	
P-027	No-load running torque	T	65 μNm	
P-028	Rated running torque	T	620 μNm	
P-034	Lifetime for rated operation		1000 h	
P-035	Radial backlash output shaft		0 μm	
P-036	Axial backlash output shaft		0 μm	
P-037	Radial stiffness	c	0.87 N/ μm	
P-038	Axial stiffness	c	18.5 $\frac{\text{N}}{\text{m}}$	
P-039	Max. radial load on output shaft (non-operating, constant load)	F	20 N	
P-040	Max. radial load on output shaft (non-operating, impulsive load)	F	5 N	
P-041	Max. radial load on output shaft (operating, constant load)	F	3 N	
P-042	Max. radial load on output shaft (operating, impulsive load)	F	3 N	
P-043	Max. axial load on output shaft (non-operating, constant load)	F	64 N	
P-044	Max. axial load on output shaft (non-operating, impulsive load)	F	20 N	

Technical Supply Specifications: MaalonDrive® Hollow 8mm - Type 2



Micromotion GmbH, Phone: +49 (0) 6431 – 569 18 – 25, E-mail: sales@micromotion.de

Nr.	Parameter	Symbol	Value	Hint
P-045	Max. axial load on output shaft (operating, constant load)	F	185 N	
P-046	Max. axial load on output shaft (operating, impulsive load)	F	66 N	
P-047	Max. radial load on input shaft (non-operating, constant load)	F	25 N	
P-048	Max. radial load on input shaft (non-operating, impulsive load)	F	8 N	
P-049	Max. radial load on input shaft (operating, constant load)	F	11 N	
P-050	Max. radial load on input shaft (operating, impulsive load)	F	8 N	
P-051	Max. axial load on input shaft (non-operating, constant load)	F	49 N	
P-052	Max. axial load on input shaft (non-operating, impulsive load)	F	15 N	
P-053	Max. axial load on input shaft (operating, constant load)	F	147.5 N	
P-054	Max. axial load on input shaft (operating, impulsive load)	F	61 N	
P-055	Moment of inertia	I	28 * 10 ⁻⁴ gcm ²	
P-056	Weight	m	4 g	
P-057	Min. permissible ambient temperature (non-operating)	T	-80 °C	
P-058	Min. permissible ambient temperature (operating)	T	-20 °C	
P-059	Max. permissible ambient temperature (non-operating)	T	150 °C	
P-060	Max. permissible ambient temperature (operating)	T	120 °C	

Material information

Nr.	Parameter	Symbol	Value	Hint
P-900	RoHS compliant		yes	
P-901	Lubrication of output bearing gearbox		Asonic GLY32	
P-902	Lubrication of input bearing gearbox		Longtime PD2	
P-908	Material of gear component set		NiFe	
P-909	Material of output bearing gearbox		1.4108 DIN EN	
P-910	Material of input bearing gearbox		1.4108 DIN EN	
P-912	Material of gearbox output side		1.4305 DIN EN	


Technical Supply Specifications: MaalonDrive® Hollow 8mm - Type 2



Micromotion GmbH, Phone: +49 (0) 6431 – 569 18 – 25, E-mail: sales@micromotion.de

Nr.	Parameter	Symbol	Value	Hint
P-913	Material of gearbox input side		1.4305 DIN EN	

Technical drawing



Micromotion GmbH | Hoenbergstraße 14 | 65555 Limburg
+49(0)6431-59618-25 | sales@micromotion.de | www.micromotion-drives.com